

Jasart Byron WC Pocket Landscape Set 12

Jasco Pty Limited

Chemwatch Hazard Alert Code: 3

Chemwatch: 5475-03

Issue Date: 29/06/2021

Version No: 2.1.8.8

Print Date: 08/07/2021

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

L.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Jasart Byron WC Pocket Landscape Set 12
Chemical Name	Not Applicable
Synonyms	78380
Proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains C.I. Pigment Blue 29)
Chemical formula	Not Applicable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Jasco Pty Limited
Address	1-5 Commercial Road Kingsgrove NSW 2208 Australia
Telephone	+61 2 9807 1555
Fax	Not Available
Website	www.jasco.com.au
Email	sales@jasco.com.au

Emergency telephone number

Association / Organisation	Australian Poisons Centre
Emergency telephone numbers	13 11 26 (24/7)
Other emergency telephone numbers	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 1, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation), Acute Aquatic Hazard Category 1
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
---------------------	---

Jasart Byron WC Pocket Landscape Set 12

Signal word	Danger
-------------	--------

Hazard statement(s)

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P391	Collect spillage.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
471-34-1	>60	<u>calcium carbonate</u>
57455-37-5	<50	<u>C.I. Pigment Blue 29</u>
9004-53-9	<30	<u>dextrins</u>
51274-00-1	<30	<u>C.I. Pigment Yellow 42</u>
3520-72-7	<10	<u>C.I. Pigment Orange 13</u>
2512-29-0	<10	<u>C.I. Pigment Yellow 1</u>
1333-86-4	<10	<u>C.I. Pigment Black 7</u>
13463-67-7	<3	<u>C.I. Pigment White 6</u>
Not Available	balance	Ingredients determined not to be hazardous

Legend: 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available

SECTION 4 First aid measures

Description of first aid measures

Continued...

Jasart Byron WC Pocket Landscape Set 12

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay.
Ingestion	<ul style="list-style-type: none"> ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

Special hazards arising from the substrate or mixture

Fire Incompatibility	<ul style="list-style-type: none"> ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	<ul style="list-style-type: none"> ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ Use water delivered as a fine spray to control fire and cool adjacent area. ▶ Avoid spraying water onto liquid pools. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire.
Fire/Explosion Hazard	<p>For starch/ air mixtures Starch is a class St1 dust at normal moisture level: Minimum Ignition Temperature (MIE): >30 mJ at normal moisture level Pmax 9.5 Bar Kst 170 bar.m/s Layer Ignition Temperature: >450 deg C Autoignition Temperature: 170 deg C (above this temperature starch will self-heat)</p> <p>Dust Explosion Hazard Class 1</p> <p>Dusts fall into one of three Kst* classes. Class 1 dusts; Kst 1-200 m3/sec; Class 2 dusts; 201-299 m3/sec. Class 3 dusts; Kst 300 or more. Most agricultural dusts (grains, flour etc.) are Class 1; pharmaceuticals and other speciality chemicals are typically Class 1 or 2; most unoxidised metallic dusts are Class 3. The higher the Kst, the more energetically the dust will burn and the greater is the explosion risk and the greater is the speed of the explosion.. Standard test conditions, used to derive the Kst, are representative of industrial conditions, but do not represent and absolute</p>

Jasart Byron WC Pocket Landscape Set 12

worst case. Increased levels of turbulence increase the speed of the explosion dramatically.

* Kst - a normalised expression of the burning dust pressure rise rate over time.

Dusts with Minimum Ignition Energies (MIEs) ranging between 20 and 100 mJ may be sensitive to ignition. They require that:

- plant is grounded
- personnel might also need to be grounded
- the use of high resistivity materials (such as plastics) should be restricted or avoided during handling or in packaging

The majority of ignition accidents occur within or below this range.

The MIE of a dust/air mix depends on the particle size the water content and the temperature of the dust. The finer and the dryer the dust the lower the MIE. Higher temperatures cause lower MIE and an increased risk of dust explosion.

Quoted values for MIE generally are only representative. Characteristics may change depending upon the process and conditions of use or any changes made to the dust during use, including further grinding or mixing with other products. In order to obtain more specific data for dust, as used, it is recommended that further characterisation testing is performed.

- Combustible.
- Slight fire hazard when exposed to heat or flame.
- Heating may cause expansion or decomposition leading to violent rupture of containers.
- On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- Mists containing combustible materials may be explosive.

Combustion products include:

carbon dioxide (CO₂)
nitrogen oxides (NO_x)
silicon dioxide (SiO₂)
hydrogen sulfide (H₂S)
metal oxides
other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

Heating calcium carbonate at high temperatures(825 C.) causes decomposition, releases carbon dioxide gas and leaves a residue of alkaline lime

HAZCHEM •3Z

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<ul style="list-style-type: none"> ▸ Remove all ignition sources. ▸ Clean up all spills immediately. ▸ Avoid breathing vapours and contact with skin and eyes. ▸ Control personal contact with the substance, by using protective equipment. ▸ Contain and absorb spill with sand, earth, inert material or vermiculite. ▸ Wipe up. ▸ Place in a suitable, labelled container for waste disposal.
Major Spills	<ul style="list-style-type: none"> ▸ Clear area of personnel and move upwind. ▸ Alert Fire Brigade and tell them location and nature of hazard. ▸ Wear full body protective clothing with breathing apparatus. ▸ Prevent, by all means available, spillage from entering drains or water courses. ▸ Consider evacuation (or protect in place). ▸ No smoking, naked lights or ignition sources. ▸ Increase ventilation. ▸ Stop leak if safe to do so. ▸ Water spray or fog may be used to disperse / absorb vapour. ▸ Contain or absorb spill with sand, earth or vermiculite. ▸ Collect recoverable product into labelled containers for recycling. ▸ Collect solid residues and seal in labelled drums for disposal. ▸ Wash area and prevent runoff into drains. ▸ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using. ▸ If contamination of drains or waterways occurs, advise emergency services.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of exposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps. ▶ DO NOT enter confined spaces until atmosphere has been checked. ▶ Avoid smoking, naked lights or ignition sources. ▶ Avoid contact with incompatible materials. ▶ When handling, DO NOT eat, drink or smoke. ▶ Keep containers securely sealed when not in use. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. ▶ Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights or ignition sources. ▶ Store in a cool, dry, well-ventilated area. ▶ Store away from incompatible materials and foodstuff containers. ▶ Protect containers against physical damage and check regularly for leaks. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Polyethylene or polypropylene container. ▶ Packing as recommended by manufacturer. ▶ Check all containers are clearly labelled and free from leaks.
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid reaction with oxidising agents, bases and strong reducing agents. ▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	calcium carbonate	Calcium carbonate	10 mg/m ³	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.
Australia Exposure Standards	C.I. Pigment Black 7	Carbon black	3 mg/m ³	Not Available	Not Available	Not Available
Australia Exposure Standards	C.I. Pigment White 6	Titanium dioxide	10 mg/m ³	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
calcium carbonate	45 mg/m ³	210 mg/m ³	1,300 mg/m ³
C.I. Pigment Black 7	9 mg/m ³	99 mg/m ³	590 mg/m ³
C.I. Pigment White 6	30 mg/m ³	330 mg/m ³	2,000 mg/m ³

Ingredient	Original IDLH	Revised IDLH
calcium carbonate	Not Available	Not Available
C.I. Pigment Blue 29	Not Available	Not Available
dextrins	Not Available	Not Available
C.I. Pigment Yellow 42	Not Available	Not Available
C.I. Pigment Orange 13	Not Available	Not Available
C.I. Pigment Yellow 1	Not Available	Not Available
C.I. Pigment Black 7	1,750 mg/m ³	Not Available

Jasart Byron WC Pocket Landscape Set 12

Ingredient	Original IDLH	Revised IDLH
C.I. Pigment White 6	5,000 mg/m ³	Not Available

Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
C.I. Pigment Yellow 42	E	≤ 0.01 mg/m ³
C.I. Pigment Orange 13	C	> 0.1 to ≤ milligrams per cubic meter of air (mg/m ³)
C.I. Pigment Yellow 1	E	≤ 0.01 mg/m ³

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Exposure controls

<p>Appropriate engineering controls</p>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <ul style="list-style-type: none"> ▶ Employees exposed to confirmed human carcinogens should be authorized to do so by the employer, and work in a regulated area. ▶ Work should be undertaken in an isolated system such as a "glove-box" . Employees should wash their hands and arms upon completion of the assigned task and before engaging in other activities not associated with the isolated system. ▶ Within regulated areas, the carcinogen should be stored in sealed containers, or enclosed in a closed system, including piping systems, with any sample ports or openings closed while the carcinogens are contained within. ▶ Open-vessel systems are prohibited. ▶ Each operation should be provided with continuous local exhaust ventilation so that air movement is always from ordinary work areas to the operation. ▶ Exhaust air should not be discharged to regulated areas, non-regulated areas or the external environment unless decontaminated. Clean make-up air should be introduced in sufficient volume to maintain correct operation of the local exhaust system. ▶ For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood. ▶ Except for outdoor systems, regulated areas should be maintained under negative pressure (with respect to non-regulated areas). ▶ Local exhaust ventilation requires make-up air be supplied in equal volumes to replaced air. ▶ Laboratory hoods must be designed and maintained so as to draw air inward at an average linear face velocity of 0.76 m/sec with a minimum of 0.64 m/sec. Design and construction of the fume hood requires that insertion of any portion of the employees body, other than hands and arms, be disallowed. <p>Assess operations based upon available dust explosion information to determine the suitability of preventative or protective systems as precautionary measures against possible dust explosions. If prevention is not possible, consider protection by use of containment, venting or suppression of dust handling equipment. Where explosion venting is considered to be the most appropriate method of protection, vent areas should preferably be calculated based on Kst rather than an St value. If nitrogen purging is considered as the protective system, it must operate with an oxygen level below the limiting oxygen concentration. The system should include an oxygen monitoring and shut-down facility in the event of excessive oxygen being detected.</p> <p>The maximum surface temperature of enclosures potentially exposed to this material should be based on values obtained by taking 2/3 of the minimum ignition temperature (MIE) of the dust cloud. The effect of dust layers should be reviewed.</p> <p>An isolated (insulated) human body can readily produce electrostatic discharges in excess of 50 mJ, but have been recorded up to 100 mJ.</p>
<p>Personal protection</p>	
<p>Eye and face protection</p>	<ul style="list-style-type: none"> ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Jasart Byron WC Pocket Landscape Set 12

	<p>Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</p>
Skin protection	<p>See Hand protection below</p>
Hands/feet protection	<ul style="list-style-type: none"> ▶ Wear chemical protective gloves, e.g. PVC. ▶ Wear safety footwear or safety gumboots, e.g. Rubber <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> · frequency and duration of contact, · chemical resistance of glove material, · glove thickness and · dexterity <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> · When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended. · Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use. · Contaminated gloves should be replaced. <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> · Excellent when breakthrough time > 480 min · Good when breakthrough time > 20 min · Fair when breakthrough time < 20 min · Poor when glove material degrades <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p>
Body protection	<p>See Other protection below</p>
Other protection	<ul style="list-style-type: none"> ▶ Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent] ▶ Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent] ▶ Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely. ▶ Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood. ▶ Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood. ▶ Overalls. ▶ P.V.C apron. ▶ Barrier cream. ▶ Skin cleansing cream. ▶ Eye wash unit.

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-
up to 100 x ES	-	A-2	A-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- Where protection from nuisance levels of dusts are desired, use type N95 (US) or type P1 (EN143) dust masks. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU)
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- Try to avoid creating dust conditions.

Where significant concentrations of the material are likely to enter the breathing zone, a Class P3 respirator may be required.

Class P3 particulate filters are used for protection against highly toxic or highly irritant particulates.

Filtration rate: Filters at least 99.95% of airborne particles

Suitable for:

- Relatively small particles generated by mechanical processes eg. grinding, cutting, sanding, drilling, sawing.
- Sub-micron thermally generated particles e.g. welding fumes, fertilizer and bushfire smoke.
- Biologically active airborne particles under specified infection control applications e.g. viruses, bacteria, COVID-19, SARS
- Highly toxic particles e.g. Organophosphate Insecticides, Radionuclides, Asbestos

Note: P3 Rating can only be achieved when used with a Full Face Respirator or Powered Air-Purifying Respirator (PAPR). If used with any other respirator, it will only provide filtration protection up to a P2 rating.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Various colored and shaped solid containing watercolor pan set.		
Physical state	Liquid	Relative density (Water = 1)	1.5-2.0
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7.0-8.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available

Continued...

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Not Available	pH as a solution (%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	<p>Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p>
Ingestion	<p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Starch has such a low oral acute toxicity that rats given 10-20% of their body weight, show only minimal effects. This may not be true of modified starches but given their use in foods as stabilisers and thickeners, there is probably little cause for concern.</p> <p>An abnormal craving for starch (amylophagia), during pregnancy, is recognised as a common form of eating disorder in certain localities. In one study the incidence was as high as 35%. Some women retain the habit for years and may ingest several kilograms of starch daily.</p> <p>Since starch, in such "addicts", accounts for the bulk of the diet, the commonly observed <i>iron-deficiency anaemia</i> is probably the result of the practice and not its cause. Less common complications include parotid gland enlargement and partial intestinal obstruction due to starch concretions (gastroliths). Withdrawal reverse these sequelae.</p>
Skin Contact	<p>The material produces moderate skin irritation; evidence exists, or practical experience predicts, that the material either</p> <ul style="list-style-type: none"> ▶ produces moderate inflammation of the skin in a substantial number of individuals following direct contact, and/or ▶ produces significant, but moderate, inflammation when applied to the healthy intact skin of animals (for up to four hours), such inflammation being present twenty-four hours or more after the end of the exposure period. <p>Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
Eye	<p>When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.</p>
Chronic	<p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.</p> <p>On the basis of epidemiological data, the material is regarded as carcinogenic to humans. There is sufficient data to establish a causal association between human exposure to the material and the development of cancer.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> <p>Some workers may develop chronic occupational dermatitis (generally mild) through the handling of starch products.</p> <p>When starch is used as a lubricant in surgical gloves, small amounts, released into the patient during the course of surgery, have</p>

resulted in granulomas and peritonitis.

Many azo dyes have been found to be carcinogenic in laboratory animals, affecting the liver, urinary bladder and intestines. Specific toxicity effects in humans have not been established but some dyes are known to be mutagenic.

The simplest azo dyes, which raise concern, have an exocyclic amino-group that is the key to any carcinogenicity for it is this group which undergoes biochemical N-oxidation and further reaction to reactive electrophiles. The DNA adducts formed by covalent binding through activated nitrogen have been identified. However not all azo compounds possess this activity and delicate alterations to structure vary the potential of carcinogenicity / acid, reduces or eliminates the effect. Complex azo dyes consisting of more than one azo (N=N) linkage may be metabolised to produce complexed carcinogenic aromatic amines such as benzidine

Benzidine and its metabolic derivatives have been detected in the urine of workers exposed to Direct azo dyes. An epidemiological study of silk dyers and painters with multiple exposures to benzidine based and other dyes indicate a strong association with bladder cancer.

Most organic azo dyes are potential skin sensitisers, the most important of which are para-phenylenediamine and its analogs. Water soluble azo dyes are more likely to cause clinical sensitisation than insoluble dyes. In addition to allergic eczematous contact dermatitis, color developing solutions have caused lichen planus like eruptions

Pure calcium carbonate does not produce pneumoconiosis probably being eliminated from the lungs slowly by solution.

As mined, unsterilised particulates can carry bacteria into the air passages and lungs, producing infection and bronchitis.

High blood concentrations of calcium ion may give rise to vasodilation and depress cardiac function leading to hypotension and syncope. Calcium ions enhance the effects of digitalis on the heart and may precipitate digitalis intoxication. Calcium salts also reduce the absorption of tetracyclines

In neonates calcification of soft-tissue has been observed following therapeutic administration.

Some studies show that large quantities of calcium intake can cause hypercalcemia, which can in turn lead to renal failure. Renal failure can occur within hours or days or, alternatively, settles gradually, evolving over several years until it reaches terminal stages. Similarly, acute renal failure can also develop into chronic forms of the disease.

Hypercalcaemia conditions can be associated with normal or reduced calcium serum levels, as the body tends to maintain a balanced metabolism of the mineral, known as the compensation phase. When there is a slight increase in the concentration of ions in the blood, calcium excretion markedly increases, while intestinal absorption decreases. After kidney damage has set in, a loss of calcium may occur, thereby decreasing the serum concentration.

Serum protein levels may decrease as a result of proteinuria in cases of renal complications. Proteinuria is an indicator of kidney disease and represents an independent risk factor for the progression of such a condition. Increased serum creatinine levels may represent an important parameter, given that kidney diseases are associated with increased serum creatinine levels. When renal pathology occurs, a progressive loss of glomerular filtration begins, resulting in increased plasma creatinine concentrations.

During the course of kidney failure, discrete, but constant, increments in plasma creatinine levels occur.

Renal disease with albuminuria may also be the cause of hypoalbuminemia in patients with liver disease. In cases of established liver damage, increased calcium urinary excretion may occur. Therefore, a similar increase may cause the decline in serum calcium levels in the current study.

Chronic excessive iron exposure has been associated with haemosiderosis and consequent possible damage to the liver and pancreas. Haemosiderin is a golden-brown insoluble protein produced by phagocytic digestion of haematin (an iron-based pigment). Haemosiderin is found in most tissues, especially in the liver, in the form of granules. Other sites of haemosiderin deposition include the pancreas and skin. A related condition, haemochromatosis, which involves a disorder of metabolism of these deposits, may produce cirrhosis of the liver, diabetes, and bronze pigmentation of the skin - heart failure may eventually occur.

Such exposure may also produce conjunctivitis, choroiditis, retinitis (both inflammatory conditions involving the eye) and siderosis of tissues if iron remains in these tissues. Siderosis is a form of pneumoconiosis produced by iron dusts. Siderosis also includes discoloration of organs, excess circulating iron and degeneration of the retina, lens and uvea as a result of the deposition of intraocular iron. Siderosis might also involve the lungs - involvement rarely develops before ten years of regular exposure. Often there is an accompanying inflammatory reaction of the bronchi. Permanent scarring of the lungs does not normally occur.

High levels of iron may raise the risk of cancer. This concern stems from the theory that iron causes oxidative damage to tissues and organs by generating highly reactive chemicals, called free radicals, which subsequently react with DNA. Cells may be disrupted and may become cancerous. People whose genetic disposition prevents them from keeping tight control over iron (e.g. those with the inherited disorder, haemochromatosis) may be at increased risk.

Iron overload in men may lead to diabetes, arthritis, liver cancer, heart irregularities and problems with other organs as iron builds up.

[K. Schmidt, New Scientist, No. 1919 pp.11-12, 2nd April, 1994]

Jasart Byron WC Pocket Landscape Set 12	TOXICITY	IRRITATION
	Not Available	Not Available
calcium carbonate	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.75 mg/24h - SEVERE
	Inhalation(Rat) LC50; >3 mg/4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral(Rat) LD50; >2000 mg/kg ^[1]	Skin (rabbit): 500 mg/24h-moderate
		Skin: no adverse effect observed (not irritating) ^[1]
C.I. Pigment Blue 29	TOXICITY	IRRITATION
	Oral(Rat) LD50; >10000 mg/kg ^[2]	Not Available

dextrins	TOXICITY	IRRITATION
	Oral(Rat) LD50; >2000 mg/kg ^[2]	Not Available
C.I. Pigment Yellow 42	TOXICITY	IRRITATION
	Oral(Rat) LD50; >5000 mg/kg ^[2]	Not Available
C.I. Pigment Orange 13	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral(Rat) LD50; >2100 mg/kg ^[1]	Not Available
C.I. Pigment Yellow 1	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral(Rat) LD50; >2000 mg/kg ^[1]	Non-irritating/non-sensitising
C.I. Pigment Black 7	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg ^[1] Oral(Rat) LD50; >8000 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1] Skin: no adverse effect observed (not irritating) ^[1]
C.I. Pigment White 6	TOXICITY	IRRITATION
	dermal (hamster) LD50: >=10000 mg/kg ^[2] Inhalation(Rat) LC50; >2.28 mg/l4h ^[1]	Eye: no adverse effect observed (not irritating) ^[1] Skin (rabbit)
	Oral(Rat) LD50; >=2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

CALCIUM CARBONATE	No evidence of carcinogenic properties. No evidence of mutagenic or teratogenic effects. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.
C.I. PIGMENT BLUE 29	NOTE: 90 day (chronic), teratological and mutagenicity tests here all provided negative results. Animal tests have also demonstrated no skin irritation or sensitization. [IC]
C.I. PIGMENT ORANGE 13	For diarylide (disazo) pigments (3,3'-dichlorobenzidine-containing): The substances in this category do not present a hazard for human health due to their low hazard profile. Adequate screening-level data are available to characterise the human health hazard for the purposes of the OECD Cooperative Chemicals Assessment Programme. Diarylide pigments are synthesized by bis-diazotizing diamino-diphenyl derivatives, mainly 3,3'-dichlorobenzidine (DCB), and coupling with acetoacetylides or arylsubstituted pyrazolones Studies indicate that essentially there is no potential for uptake via the oral and dermal routes. However, following repeated oral exposure at high dose levels, there is some evidence that a very limited uptake of the compound (or its impurities) could occur, based on observations of staining of the mucosal surfaces of internal organs (although the possibility of contamination during necropsy cannot be excluded). In an oral reproductive developmental screening study, staining of the pups could indicate a potential for limited placental transfer, again at a high dose level. Given that the Pigment Yellows are essentially not absorbed into the body, metabolism is not relevant. However, the presence of very low levels of 3,3'-dichlorobenzidine has been demonstrated in two studies using very sensitive techniques following oral administration of some yellow pigment compounds. It seems likely that this is due to the presence of a mono-azo impurity in some of the yellow pigment parent compounds, which is absorbed and subsequently metabolised. No DCB was found in the urine of experimental animals after exposure orally or via the lungs in long term studies. Following ingestion, the vast majority of the pigments are excreted unchanged in the faeces. Many diarylide pigments are derived from DCB. Therefore, the diarylide pigments on DCB basis have been tested toxicologically very extensively. Diarylide pigments with their LD50 values above 2 000 mg/kg show no acute toxicity according to the EU classification criteria. They are not irritating to the skin or mucous membranes. For acute dermal toxicity a single LD50 of >3,000 mg/kg bw is available for Pigment Yellow 13. No deaths or clinical signs of toxicity were observed following oral or dermal exposure. The inhalation LC50 available is >4,448 mg/m ³ for Pigment Yellow 13. Tachypnoea, dyspnoea, exophthalmos, ruffled fur and curved or ventral body position were observed, although all animals recovered and no gross abnormalities were observed at necropsy. Based on the available data the pigments have a minimal to slight potential for eye irritation. There is no indication that they are sensitisers No adverse effects were seen after 4-7 weeks oral administration of Pigment Yellow 12 at 1000 mg/kg/day (NOAEL), the highest dose tested in a well conducted and reported test of repeated dose toxicity study. Furthermore, in the cases of Pigment Yellow 12 and 83, no toxicologically significant effects were observed in a range of chronic toxicity studies of lesser quality (in terms of reporting) in rats and mice at doses up to 6500 mg/kg/day. Based on the kinetics of the three pigments and the chemical

similarities, it can be concluded that these findings can be extrapolated to most if not all diarylide pigments.

For the inhalation route the effects seen are related to the deposition of dust particles in the lungs, leading to Pigment Yellow 13 related effects even at the lowest exposure concentration of 54 mg/m³ (local LOAEL). Systemically no effects were observed at the highest concentration tested, 410 mg/m³ (systemic NOAEL).

All three pigments are not genotoxic in bacterial tests. Pigment Yellow 12 did not induce clastogenic effects in mammalian cells. Based on the chemical similarities between the three pigments, it is predicted that all three Yellow Pigments will not induce chromosomal changes in mammalian cells. There are no in vitro data to suggest that the pigments are genotoxic in vivo.

No increased tumour incidence after treatment with Pigment Yellow 12 and 83 were observed in several long-term studies in rats and mice (NOAEL (rat) > 630 mg/kg; NOAEL (mouse) > 1,960 mg/kg). Based on chemical similarity it can be concluded that the pigments are not carcinogenic.

It can be concluded that Pigment Yellow 12 does not have any adverse effects on reproductive parameters. There was no evidence of teratogenicity. The NOAEL for maternal and reproductive toxicity is >1,000 mg/kg bw. Supporting evidence is also available from the fact that no changes on the reproductive organs were observed in the studies of repeat dose toxicity and carcinogenicity study with Pigment Yellow 83. In view of the structural similarities and similar kinetics no effects on reproduction or development are expected from pigments of this class.

In studies of the bioavailability of several representatives of this group of pigments, no carcinogenic cleavage product was released in detectable amounts after oral, inhalative or intratracheal application on rats.

One further study of the bioavailability of DCB (DCB haemoglobin adduct) has been performed with the diarylide pigments C.I. Pigment Yellow 13 and C.I. Pigment Yellow 17. In this study, no release of carcinogenic DCB from the pigments has been detected. This indicates the absence of metabolism to DCB under the test conditions.

In summary then, according to the known studies, diarylide pigments do not represent any health risk although risks might attach to contaminants introduced during synthesis.

Colourants for Food Contact Plastics - Aspects of Product Safety; Responsible Care initiative of the European Chemical Industry Council.

For 3,3'-dichlorobenzidine:

Various tumours developed after oral or subcutaneous administration of 3,3'-dichlorobenzidine to mice, rats, hamsters and dogs. Tumours have not yet been identified in persons exposed to the substance alone. The substance can be absorbed through the skin in dangerous quantities. Increases in temperature and relative humidity promote dermal absorption.

Upper respiratory infection and sore throat were listed among several principal reasons for visits to a company's medical clinic by workers handling 3,3'-dichlorobenzidine dihydrochloride. However, there is no conclusive evidence that these effects were due to inhalation of 3,3'-dichlorobenzidine dihydrochloride.

No adverse health effects were observed in male rats exposed by inhalation to 3,3'-dichlorobenzidine free base (23,700 mg/m³) 2 hours per day for 7 days. In another study, 10 rats were exposed to an unspecified concentration of 3,3'-dichlorobenzidine dihydrochloride dust particles for 1 hour and then observed for 14 days. Slight-to-moderate pulmonary congestion and one pulmonary abscess were observed upon necropsy. The effects observed in the study using the ionized (hydrochloride) form of 3,3'-dichlorobenzidine may have been due to the irritative properties of hydrochloric acid released from the salt in combination with particulate toxicity.

Gastrointestinal upset was one of the symptoms reported by employees who worked with 3,3'-dichlorobenzidine dihydrochloride. However, there is no conclusive evidence that the gastrointestinal effects, or other symptoms reported by employees, resulted specifically from inhalation of 3,3'-dichlorobenzidine dihydrochloride.

The only relevant information regarding neurological effects in humans exposed to 3,3'-dichlorobenzidine was found in an early study which reported that headache and dizziness were among several principal reasons why employees working with 3,3'-dichlorobenzidine in a chemical manufacturing plant visited the company medical clinic. However, there is no conclusive evidence that these symptoms were caused specifically by 3,3'-dichlorobenzidine since there was exposure to other chemicals as well. In a 3,3'-dichlorobenzidine carcinogenicity study, 1 of 6 dogs exhibited convulsions after 21, 28, or 42 months of oral treatment with 10.4 mg/kg/day over a period of 3.5 years.

Carcinogenicity: Several epidemiological studies have investigated cancer incidences among workers occupationally exposed to 3,3'-dichlorobenzidine. Exposure may have been by both inhalation and dermal routes. Due, in part, to structure-activity considerations, epidemiological studies of potential cancer effects of occupational exposure to 3,3'-dichlorobenzidine have been particularly concerned with bladder tumors, since 3,3'-dichlorobenzidine is structurally similar to benzidine, a chemical which is known to be a human bladder carcinogen. No bladder tumors were found in a group of 35 workers who handled only 3,3'-dichlorobenzidine; in the same dyestuff plant, bladder tumors occurred in 3 out of 14 workers exposed to both benzidine and 3,3'-dichlorobenzidine. The investigator reported a total exposure time of 68,505 hours, equivalent to nearly 140 full-time working years. No cases of bladder tumors were found in an epidemiology study of 259 workers exposed to dry and semidry 3,3'-dichlorobenzidine base and hydrochloride. Workers were exposed to an average of less than 16 years each to 3,3'-dichlorobenzidine, which means that an adequate exposure duration and/or the latent period following exposure may not have been reached for tumor expression.

In a retrospective epidemiological study of workers employed in a dye and pigment manufacturing plant that used 3,3'-dichlorobenzidine as chemical precursor, no bladder tumors were observed in a cohort of 207 workers, most of whom had been exposed for up to 15 years. Limitations of this study included using data from a very small and incomplete sample of workers; focusing solely on the occurrence of bladder tumors; and using data that may have been misleading and, at times, apparently inaccurate.

A statistically significant increased incidence of hepatomas was observed in male ICR/JCL mice exposed to 0.1% 3,3'-dichlorobenzidine in the diet (170 mg/kg/day) at 6 months (8 of 8 treated as opposed to 0 of 5 controls) and 12 months (18 of 18 treated as opposed to 2 of 21 controls). Hepatic tumors were observed in 4/18 strain D mice exposed to 11.2-1.9 mg 3,3'-dichlorobenzidine/kg/day in the diet for 10 months.

No bladder carcinomas were observed in rats exposed to 0.03% 3,3'-dichlorobenzidine in the diet (27 mg/kg/day) for 4 or 40 weeks, nor were any mammary tumors observed in rats administered approximately 49 mg 3,3'-dichlorobenzidine dihydrochloride/kg/day by gavage once every 3 days over a 30-day period and sacrificed 8 months later.

In a study in which rats were exposed to 10-20 mg 3,3'-dichlorobenzidine per day (120 mg/kg/day) in feed 6 days per week for 12 months, tumors were observed at a variety of sites, including the Zymbal gland (7 of 29 animals), mammary gland (7/29), bladder (3/29), hematopoietic system (3/29), skin (3/29), ileum (2/29), connective tissue (2/29), salivary gland (2/29), liver (1/29), and

thyroid (I/29).

In another rat study, 3,3'-dichlorobenzidine was administered to 50 male (70 mg/kg/day) and 50 female (80 mg/kg/day) Sprague-Dawley rats, in a standard diet for up to 16 months. In rats fed 3,3'-dichlorobenzidine in the diet for a total of 349 days (females) and 353 days (males), histopathological evaluations revealed mammary adenocarcinoma (16% incidence), malignant lymphoma (14%) granulocytic leukemia (20%), carcinoma of the Zymbal gland (18%) in males, and mammary adenocarcinoma (59%) in females. The authors noted that most of these tumors appeared to arise in the bone marrow and haematopoietic foci in the spleen and liver with subsequent metastasis to other organs.

Haematological Effects. Although haematological effects may not be sensitive indicators for 3,3'-dichlorobenzidine toxicity, haemoglobin adducts have been detected in female Wistar rats orally administered single 127 or 253 mg/kg doses of 3,3'-dichlorobenzidine or with repeated doses between 0.3 and 5.8 mg/kg/day. It was suggested that metabolically formed nitroso derivatives and the formation of a sulfinic acid amide with cysteine residues in haemoglobin may be the mechanism of adduct formation.

Hepatic Effects. Limited animal evidence suggests that chronic-duration oral exposure to 3,3'-dichlorobenzidine results in mild-to-moderate liver injury.

Genotoxic effects: Genotoxic effects have been reported in animals treated with 3,3'-dichlorobenzidine. A single dose of 3,3'-dichlorobenzidine (1,000 mg/kg) administered to male and pregnant female mice induced micronuclei in polychromatic erythrocytes in the bone marrow of the males and in the liver of the foetuses, but not in bone marrow of the dams.

In another study, an increase in unscheduled deoxyribonucleic acid synthesis (UDS) was observed in cultured liver cells from male mice previously pretreated orally with single doses of . 500 mg/kg 3,3'-dichlorobenzidine; no response was observed at a dose of .200 mg/kg. 3,3'-Dichlorobenzidine was also shown to bind extensively to tissue deoxyribonucleic acid (DNA) in rats and mice

In vitro screening test for mutagenicity: negative

For titanium dioxide:

Humans can be exposed to titanium dioxide via inhalation, ingestion or dermal contact. In human lungs, the clearance kinetics of titanium dioxide is poorly characterized relative to that in experimental animals. (General particle characteristics and host factors that are considered to affect deposition and retention patterns of inhaled, poorly soluble particles such as titanium dioxide are summarized in the monograph on carbon black.) With regard to inhaled titanium dioxide, human data are mainly available from case reports that showed deposits of titanium dioxide in lung tissue as well as in lymph nodes. A single clinical study of oral ingestion of fine titanium dioxide showed particle size-dependent absorption by the gastrointestinal tract and large interindividual variations in blood levels of titanium dioxide. Studies on the application of sunscreens containing ultrafine titanium dioxide to healthy skin of human volunteers revealed that titanium dioxide particles only penetrate into the outermost layers of the stratum corneum, suggesting that healthy skin is an effective barrier to titanium dioxide. There are no studies on penetration of titanium dioxide in compromised skin.

Respiratory effects that have been observed among groups of titanium dioxide-exposed workers include decline in lung function, pleural disease with plaques and pleural thickening, and mild fibrotic changes. However, the workers in these studies were also exposed to asbestos and/or silica.

No data were available on genotoxic effects in titanium dioxide-exposed humans.

Many data on deposition, retention and clearance of titanium dioxide in experimental animals are available for the inhalation route. Titanium dioxide inhalation studies showed differences — both for normalized pulmonary burden (deposited mass per dry lung, mass per body weight) and clearance kinetics — among rodent species including rats of different size, age and strain. Clearance of titanium dioxide is also affected by pre-exposure to gaseous pollutants or co-exposure to cytotoxic aerosols.

Differences in dose rate or clearance kinetics and the appearance of focal areas of high particle burden have been implicated in the higher toxic and inflammatory lung responses to intratracheally instilled vs inhaled titanium dioxide particles. Experimental studies with titanium dioxide have demonstrated that rodents experience dose-dependent impairment of alveolar macrophage-mediated clearance. Hamsters have the most efficient clearance of inhaled titanium dioxide. Ultrafine primary particles of titanium dioxide are more slowly cleared than their fine counterparts.

Titanium dioxide causes varying degrees of inflammation and associated pulmonary effects including lung epithelial cell injury, cholesterol granulomas and fibrosis. Rodents experience stronger pulmonary effects after exposure to ultrafine titanium dioxide particles compared with fine particles on a mass basis. These differences are related to lung burden in terms of particle surface area, and are considered to result from impaired phagocytosis and sequestration of ultrafine particles into the interstitium.

Fine titanium dioxide particles show minimal cytotoxicity to and inflammatory/pro-fibrotic mediator release from primary human alveolar macrophages in vitro compared with other particles. Ultrafine titanium dioxide particles inhibit phagocytosis of alveolar macrophages in vitro at mass dose concentrations at which this effect does not occur with fine titanium dioxide. In-vitro studies with fine and ultrafine titanium dioxide and purified DNA show induction of DNA damage that is suggestive of the generation of reactive oxygen species by both particle types. This effect is stronger for ultrafine than for fine titanium oxide, and is markedly enhanced by exposure to simulated sunlight/ultraviolet light.

Animal carcinogenicity data

Pigmentary and ultrafine titanium dioxide were tested for carcinogenicity by oral administration in mice and rats, by inhalation in rats and female mice, by intratracheal administration in hamsters and female rats and mice, by subcutaneous injection in rats and by intraperitoneal administration in male mice and female rats.

In one inhalation study, the incidence of benign and malignant lung tumours was increased in female rats. In another inhalation study, the incidences of lung adenomas were increased in the high-dose groups of male and female rats. Cystic keratinizing lesions that were diagnosed as squamous-cell carcinomas but re-evaluated as non-neoplastic pulmonary keratinizing cysts were also observed in the high-dose groups of female rats. Two inhalation studies in rats and one in female mice were negative. Intratracheally instilled female rats showed an increased incidence of both benign and malignant lung tumours following treatment with two types of titanium dioxide. Tumour incidence was not increased in intratracheally instilled hamsters and female mice.

In-vivo studies have shown enhanced micronucleus formation in bone marrow and peripheral blood lymphocytes of intraperitoneally instilled mice. Increased Hprt mutations were seen in lung epithelial cells isolated from titanium dioxide-instilled rats. In another study, no enhanced oxidative DNA damage was observed in lung tissues of rats that were intratracheally instilled with titanium dioxide. The results of most in-vitro genotoxicity studies with titanium dioxide were negative.

Substance has been investigated as a mutagen, tumorigen and primary irritant.

C.I. PIGMENT WHITE 6

CALCIUM CARBONATE & C.I. PIGMENT YELLOW 42	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.
DEXTRINS & C.I. PIGMENT YELLOW 42 & C.I. PIGMENT BLACK 7	No significant acute toxicological data identified in literature search.
C.I. PIGMENT YELLOW 42 & C.I. PIGMENT WHITE 6	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✓	Reproductivity	✗
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Jasart Byron WC Pocket Landscape Set 12	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
calcium carbonate	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	6h	Fish	4-320mg/l	4
	EC50	72h	Algae or other aquatic plants	>14mg/l	2
LC50	96h	Fish	>165200mg/L	4	
C.I. Pigment Blue 29	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>99mg/l	2
	LC50	96h	Fish	>=90mg/l	2
	EC50	48h	Crustacea	>21mg/l	2
EC50(ECx)	48h	Crustacea	>21mg/l	2	
dextrins	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
C.I. Pigment Yellow 42	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Fish	0.52mg/l	2
	EC50	72h	Algae or other aquatic plants	18mg/l	2
LC50	96h	Fish	0.05mg/l	2	
C.I. Pigment Orange 13	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	0.75-5.6	7
LC50	96h	Fish	>500mg/l	2	

Continued...

Jasart Byron WC Pocket Landscape Set 12

	NOEC(ECx)	72h	Algae or other aquatic plants	1mg/l	2
C.I. Pigment Yellow 1	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>100mg/l	2
	LC50	96h	Fish	>1mg/l	2
	EC50	48h	Crustacea	>100mg/l	2
	EC10(ECx)	72h	Algae or other aquatic plants	>1mg/l	2
C.I. Pigment Black 7	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	>0.2mg/l	2
	LC50	96h	Fish	>100mg/l	2
	EC50	48h	Crustacea	33.076-41.968mg/l	4
	NOEC(ECx)	24h	Crustacea	3200mg/l	1
C.I. Pigment White 6	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	72h	Algae or other aquatic plants	3.75-7.58mg/l	4
	BCF	1008h	Fish	<1.1-9.6	7
	EC50	48h	Crustacea	1.9mg/l	2
	LC50	96h	Fish	1.85-3.06mg/l	4
	NOEC(ECx)	504h	Crustacea	0.02mg/l	4
	EC50	96h	Algae or other aquatic plants	179.05mg/l	2
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

Very toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
C.I. Pigment Yellow 1	HIGH	HIGH
C.I. Pigment White 6	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
C.I. Pigment Orange 13	LOW (BCF = 5.6)
C.I. Pigment Yellow 1	MEDIUM (LogKOW = 3.9388)
C.I. Pigment White 6	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
C.I. Pigment Yellow 1	LOW (KOC = 278.5)
C.I. Pigment White 6	LOW (KOC = 23.74)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. Otherwise: <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to
-------------------------------------	--



Continued...

Jasart Byron WC Pocket Landscape Set 12

	<p>store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</p> <ul style="list-style-type: none"> ▸ Where possible retain label warnings and SDS and observe all notices pertaining to the product. <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> ▸ Reduction ▸ Reuse ▸ Recycling ▸ Disposal (if all else fails) <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> ▸ DO NOT allow wash water from cleaning or process equipment to enter drains. ▸ It may be necessary to collect all wash water for treatment before disposal. ▸ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. ▸ Where in doubt contact the responsible authority. ▸ Recycle wherever possible or consult manufacturer for recycling options. ▸ Consult State Land Waste Authority for disposal. ▸ Bury or incinerate residue at an approved site. ▸ Recycle containers if possible, or dispose of in an authorised landfill.
--	---

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	
HAZCHEM	*3Z

Land transport (ADG)

UN number	3082	
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains C.I. Pigment Blue 29)	
Transport hazard class(es)	Class	9
	Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	274 331 335 375 AU01
	Limited quantity	5 L

Environmentally Hazardous Substances meeting the descriptions of UN 3077 or UN 3082 are not subject to this Code when transported by road or rail in;

(a) packagings;

(b) IBCs; or

(c) any other receptacle not exceeding 500 kg(L).

- Australian Special Provisions (SP AU01) - ADG Code 7th Ed.

Air transport (ICAO-IATA / DGR)

UN number	3082	
UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. * (contains C.I. Pigment Blue 29)	
Transport hazard class(es)	ICAO/IATA Class	9
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	9L
Packing group	III	

Jasart Byron WC Pocket Landscape Set 12

Environmental hazard	Environmentally hazardous	
Special precautions for user	Special provisions	A97 A158 A197 A215
	Cargo Only Packing Instructions	964
	Cargo Only Maximum Qty / Pack	450 L
	Passenger and Cargo Packing Instructions	964
	Passenger and Cargo Maximum Qty / Pack	450 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y964
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

Sea transport (IMDG-Code / GGVSee)

UN number	3082	
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (contains C.I. Pigment Blue 29)	
Transport hazard class(es)	IMDG Class	9
	IMDG Subrisk	Not Applicable
Packing group	III	
Environmental hazard	Marine Pollutant	
Special precautions for user	EMS Number	F-A , S-F
	Special provisions	274 335 969
	Limited Quantities	5 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
calcium carbonate	Not Available
C.I. Pigment Blue 29	Not Available
dextrins	Not Available
C.I. Pigment Yellow 42	Not Available
C.I. Pigment Orange 13	Not Available
C.I. Pigment Yellow 1	Not Available
C.I. Pigment Black 7	Not Available
C.I. Pigment White 6	Not Available

Transport in bulk in accordance with the ICG Code

Product name	Ship Type
calcium carbonate	Not Available
C.I. Pigment Blue 29	Not Available
dextrins	Not Available
C.I. Pigment Yellow 42	Not Available
C.I. Pigment Orange 13	Not Available
C.I. Pigment Yellow 1	Not Available
C.I. Pigment Black 7	Not Available
C.I. Pigment White 6	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

calcium carbonate is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Continued...

C.I. Pigment Blue 29 is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

dextrins is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

C.I. Pigment Yellow 42 is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

C.I. Pigment Orange 13 is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

C.I. Pigment Yellow 1 is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

C.I. Pigment Black 7 is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

C.I. Pigment White 6 is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (C.I. Pigment Blue 29; dextrins; C.I. Pigment Yellow 42; C.I. Pigment Orange 13; C.I. Pigment Yellow 1; C.I. Pigment Black 7; C.I. Pigment White 6)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	No (C.I. Pigment Yellow 42)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	29/06/2021
Initial Date	29/06/2021

SDS Version Summary

Version	Date of Update	Sections Updated
2.1.8.7	29/06/2021	Physical Properties
2.1.8.8	05/07/2021	Template Change

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit.
IDLH: Immediately Dangerous to Life or Health Concentrations
ES: Exposure Standard
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index
AIIIC: Australian Inventory of Industrial Chemicals
DSL: Domestic Substances List
NDSL: Non-Domestic Substances List
IECSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers
ENCS: Existing and New Chemical Substances Inventory
KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory
INSQ: Inventario Nacional de Sustancias Químicas
NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.