

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878  
Revision date: 26/10/2021 Supersedes version of: 17/12/2020 Version: 8.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use  
Use of the substance/mixture : Artists', craft and hobby paints

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

##### Supplier

COLART EUROPE SAS SAS  
5 rue René Panhard 72021 Le Mans Cedex 2  
72021 LeMans  
France  
T +44 208 424 3270  
[r.enquiries@colart.co.uk](mailto:r.enquiries@colart.co.uk)

##### Manufacturer

Colart France  
Zone Industrielle Nord 5 Rue René Panhard, +33 2 43 83 83 00  
Le Mans  
France  
[r.enquiries@colart.co.uk](mailto:r.enquiries@colart.co.uk)

##### Distributor

JASCO  
1-5 Commercial Road Kingsgrove  
+61- NSW 2208 New South Wales  
T 029807 1555

##### Distributor

COLART UK LTD  
Goldthorn Road  
DY11 7JN Kidderminster – Worcestershire  
United Kingdom  
T +44 (0) 2084243200  
[r.enquiries@colart.co.uk](mailto:r.enquiries@colart.co.uk)

##### Other

Colart International Holdings LTD  
The MediaWorks Building  
191 Wood Lane  
GB- W12 7FP London – London  
United Kingdom  
T 02084243200  
[r.enquiries@colart.co.uk](mailto:r.enquiries@colart.co.uk)

##### Distributor

Jasco Pty (NZ) Limited  
5 Airpark Drive, Airport Oaks, Auckland Airport Auckland  
P.O. Box 107010

#### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Australia	NSW Poisons Information Centre The Children's Hospital at Westmead	Locked Bag 4001 NSW 2145 Westmead	13 11 26	
New Zealand	New Zealand National Poison Centre Dunedin School of Medicine, University of Otago	PO Box 56 Dunedin 9054	0800 764 766 (0800 POISON)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

EUH-statements : EUH208 - Contains 2-ETHYLHEXYL ACRYLATE, 2-methylisothiazol-3(2H)-one (MIT). May produce an allergic reaction.  
Child-resistant fastening : Not applicable  
Tactile warning : Not applicable

#### 2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
OXIRANE, METHYL-, POLYMER WITH OXIRANE, MONO(3,5,5-TRIMETHYLHEXYL) ETHER	CAS-No.: 204336-40-3 EC-No.: 606-555-0	1 – 3	Aquatic Chronic 3, H412
2-ETHYLHEXYL ACRYLATE	CAS-No.: 103-11-7 EC-No.: 203-080-7	0.1 – 1	Skin Irrit. 2, H315 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Chronic 3, H412
2-methylisothiazol-3(2H)-one (MIT)	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9	< 0.1	Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Oral), H301 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410

#### Specific concentration limits:

Name	Product identifier	Specific concentration limits
2-methylisothiazol-3(2H)-one (MIT)	CAS-No.: 2682-20-4 EC-No.: 220-239-6 EC Index-No.: 613-326-00-9	( 0.0015 ≤ C ≤ 100) Skin Sens. 1A, H317

Full text of H- and EUH-statements: see section 16

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. Specific treatment is urgent (see supplemental first aid instruction on this label).
First-aid measures after skin contact	: Wash skin with plenty of water. Take off immediately all contaminated clothing. Wash with plenty of water/....
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Specific treatment (see supplemental first aid instruction on this label).
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell. Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor. Specific treatment (see supplemental first aid instruction on this label).

#### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

#### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Evacuate unnecessary personnel.
----------------------	--

##### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection.
Emergency procedures	: Ventilate area.

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13. See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.  
Storage conditions : Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use.  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight.  
Packaging materials : Do not store in corrodable metal.

### 7.3. Specific end use(s)

Refer to section 1.2.1.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

No additional information available

#### 8.1.2. Recommended monitoring procedures

No additional information available

#### 8.1.3. Air contaminants formed

No additional information available

#### 8.1.4. DNEL and PNEC

Additional information : No exposure limits exist for this material

#### 8.1.5. Control banding

No additional information available

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

##### Appropriate engineering controls:

Ensure good ventilation of the work station.

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Avoid all unnecessary exposure.

#### 8.2.2.1. Eye and face protection

##### Eye protection:

Avoid contact with eyes

#### 8.2.2.2. Skin protection

##### Hand protection:

Does not require any particular or specific measures. Respect the general rules for occupational hygiene

#### 8.2.2.3. Respiratory protection

No additional information available

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

#### Environmental exposure controls:

Avoid release to the environment.

#### Other information:

Ensure there is adequate ventilation. Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: > 100
Flammability	: Not applicable, Non flammable.
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 9 – 10
Viscosity, kinematic	: Not available
Solubility	: Miscible with water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: ≈ 1.1
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content :  $\approx 0\%$

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Thermal decomposition generates: Corrosive vapours.

### 10.2. Chemical stability

Stable under normal conditions. Not established.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates: Corrosive vapours.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Not classified pH: 9 – 10
Additional information	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Not classified pH: 9 – 10
Additional information	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified
Additional information	: Based on available data, the classification criteria are not met
STOT-single exposure	: Not classified
Additional information	: Corrosive to the respiratory tract.

### 2-ETHYLHEXYL ACRYLATE (103-11-7)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

STOT-repeated exposure : Not classified  
Additional information : Based on available data, the classification criteria are not met  
Aspiration hazard : Not classified  
Additional information : Based on available data, the classification criteria are not met

### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

No additional information available

#### 11.2.2. Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.  
Hazardous to the aquatic environment, short-term (acute) : Not classified  
Hazardous to the aquatic environment, long-term (chronic) : Not classified

### 12.2. Persistence and degradability

#### LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

Persistence and degradability	Not established.
-------------------------------	------------------

### 12.3. Bioaccumulative potential

#### LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

Bioaccumulative potential	Not established.
---------------------------	------------------

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

No additional information available

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

Additional information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN
<b>14.1. UN number or ID number</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>			
Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>			
Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available			

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

Contains no substance subject to Regulation (EU) 2019/1148 of the European Parliament and of the Council of 20 June 2019 on the marketing and use of explosives precursors.

VOC content :  $\approx 0\%$



# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### 15.1.2. National regulations

France	
Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism

#### Germany

Water hazard class (WGK) : WGK2, Significantly hazardous to water (Classification according to AwSV, Annex 1)  
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed  
SZW-lijst van mutagene stoffen : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

#### Denmark

Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product

#### Switzerland

Storage class (LK) : LK 10/12 - Liquids

#### United Kingdom/ Australia/ New Zealand

Other information : This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals.

Please read instructions/ label before using product.

#### EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555  
Police and Fire Brigade : 000  
Poisons information centre : 13 11 26  
Safety Data Sheet applicable regions : Australia

This SDS is prepared in accordance with the model Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals. Supplied as permitted by New Zealand regulations; EPA Hazardous Substances (Safety Data Sheet) notice.

Please read instructions/ label before using product.

#### EMERGENCY CONTACTS

Jasco Pty Ltd : 02 9807 1555  
Poisons information centre : 0800 764 766 (0800 POISON)  
Safety Data Sheet applicable regions : New Zealand.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

### Full text of H- and EUH-statements:

Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
---------------------------	-------------------------------------

# LIQUITEX PROFESSIONAL ACRYLIC MEDIUMS EFFECTS POURING MEDIUM GLOSS

## Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

### Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
EUH208	Contains 2-ETHYLHEXYL ACRYLATE, 2-methylisothiazol-3(2H)-one (MIT). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.